

SERIE OT

LA FLOTA



SERIE OT 1600



Máquinas lavadoras
verticales **abiertas en el lado superior**



SERIE OT 2000



Máquinas lavadoras
verticales **abiertas en el lado superior**

SERIE OT 1600

Máquinas lavadoras verticales
abiertas en el lado superior



OT 1600 200/2s	eu	0,5 - 5 m/min	350xH100 mm*	1.600 mm	3 - 15 mm opt. 3 - 19 mm	7**	5.970x1.860 xH2.520 mm	1.200 Kg	200 Kg	2
	us	19.7 - 197 "/min	13.8xH3.9 **	63 "	1/8 - 0.6 " opt. 1/8 - 0.7 "		235x73.2 xH99.2 "	2,640 lbs	441 lbs	

OT 1600 200/4s	eu	0,5 - 5 m/min	350xH100 mm*	1.600 mm	3 - 15 mm opt. 3 - 19 mm	7**	6.220x1.860 xH2.520 mm	1.200 Kg	200 Kg	4
	us	19.7 - 197 "/min	13.8xH3.9 **	63 "	1/8 - 0.6 " opt. 1/8 - 0.7 "		244.8x73.2 xH99.2 "	2,640 lbs	441 lbs	

OT 1600 300/4s	eu	0,5 - 5 m/min	350xH100 mm*	1.600 mm	3 - 20 mm opt. 3 - 30 mm	9**	6.220x1.860 xH2.520 mm	1.600 Kg	300 Kg	4
	us	19.7 - 197 "/min	13.8xH3.9 **	63 "	1/8 - 3/4 " opt. 1/8 - 1.2 "		244.8x73.2 xH99.2 "	3,527 lbs	661 lbs	

OT 1600 300/6s	eu	0,5 - 5 m/min	350xH100 mm*	1.600 mm	3 - 20 mm opt. 3 - 30 mm	9**	6.220x1.860 xH2.520 mm	1.800 Kg	300 Kg	6
	us	19.7 - 197 "/min	13.8xH3.9 **	63 "	1/8 - 3/4 " opt. 1/8 - 1.2 "		244.8x73.2 xH99.2 "	3,968 lbs	661 lbs	

OT 1600 500/4s	eu	0,5 - 5 m/min	350xH100 mm*	1.600 mm	3 - 25 mm opt. 3 - 40 mm	9**	6.710x1.860 xH2.520 mm	2.000 Kg	500 Kg	4
	us	19.7 - 197 "/min	13.8xH3.9 **	63 "	1/8 - 1 " opt. 1/8 - 1.6 "		264.1x73.2 xH99.2 "	4,409 lbs	1,102 lbs	

OT 1600 500/6s	eu	0,5 - 5 m/min	350xH100 mm*	1.600 mm	3 - 25 mm opt. 3 - 40 mm	9**	7.210x2.060 xH2.520 mm	2.300 Kg	500 Kg	6
	us	19.7 - 197 "/min	13.8xH3.9 **	63 "	1/8 - 1 " opt. 1/8 - 1.6 "		283.8x81.1 xH99.2 "	5,070 lbs	1,102 lbs	

SERIE OT 2000

Máquinas lavadoras verticales abiertas en el lado superior



OT 2000/300/4s	eu	0,5 - 5 m/min	350xH100 mm*	2.000 mm	3 - 20 mm opt. 3 - 30 mm	9**	6.220x1.860 xH2.920 mm	2.000 Kg	300 Kg	4
	us	19.7 - 197 "/min	13.8xH3.9 **	78.7 "	1/8 - 3/4 " opt. 1/8 - 1.2 "		244.8x73.2 xH114.9 "	4,409 lbs	661 lbs	

OT 2000/300/6s	eu	0,5 - 5 m/min	350xH100 mm*	2.000 mm	3 - 20 mm opt. 3 - 30 mm	9**	6.710x1.860 xH2.920 mm	2.000 Kg	300 Kg	6
	us	19.7 - 197 "/min	13.8xH3.9 **	78.7 "	1/8 - 3/4 " opt. 1/8 - 1.2 "		264.1x73.2 xH114.9 "	4,409 lbs	661 lbs	

OT 2000/500/4s	eu	0,5 - 5 m/min	350xH100 mm*	2.000 mm	3 - 25 mm opt. 3 - 40 mm	14**	6.710x1.860 xH2.920 mm	2.400 Kg	500 Kg	4
	us	19.7 - 197 "/min	13.8xH3.9 **	78.7 "	1/8 - 1 " opt. 1/8 - 1.6 "		264.1x73.2 xH114.9 "	5,291 lbs	1,102 lbs	

OT 2000/500/6s	eu	0,5 - 5 m/min	350xH100 mm*	2.000 mm	3 - 25 mm opt. 3 - 40 mm	14**	7.210x2.060 xH2.920 mm	2.700 Kg	500 Kg	6
	us	19.7 - 197 "/min	13.8xH3.9 **	78.7 "	1/8 - 1 " opt. 1/8 - 1.6 "		283.8x81.1 xH114.9 "	5,952 lbs	1,102 lbs	

* otras a petición
** estándar (puede variar en función de cualquier elemento opcional incluido)